



R 63 BR

Cast iron wheel, coated with excellent quality vulcanized molded rubber. It presents a good frontal shock resistance and also allows a good floor protection. It is commonly known due to the wide range of diameters available. As main application, it can be used in either mechanically or manually operated equipment, and may be supplied with STANDARD OR SPECIAL RUBBER.

Hardness: 70 (± 5) Shore A.

Color: Black.

Temperature range: from -40° up to 70° C.

						Ref. Wheel		
3"	1.1/4"	5/16"	37		60	R 312 BN		
4"	1.1/2"	7/16"	47		120	R 414 BN		
5"					140	R 514 BN		
6"					150	R 614 BN		
4"					120	R 414 BR		
5"					140	R 514 BR		
6"					150	R 614 BR		
4"	2"	5/8"	62			150	R 42 BR	
5"						175	R 52 BR	
6"						220	R 62 BR	
7"						250	R 72 BR	
8"						275	R 82 BR	
9"				275		R 92 BR		
10"	375	R 102 BR						
6"	70	1"	78	300		R 63 BR		
8"				400		R 83 BR		
10"				450		R 103 BR		
12"				600		R 123 BR		
6"				100		110	450	R 64 BR
8"					600		R 84 BR	
4"	2"	62			150		R 42 BE	
5"					175		R 52 BE	
6"					220		R 62 BE	
7"					250		R 72 BE	
8"				275	R 82 BE			
9"				275	R 92 BE			
10"	375	R 102 BE						
6"	70	25		78	300	R 63 BE		
8"					400	R 83 BE		
10"					450	R 103 BE		
12"					600	R 123 BE		
6"					100	25	110	450
8"			600					R 84 BE
10"	700	R 104 BE						
12"	900	R 124 BE						
16"	125	35	134	1400				R 165 BE

