

P – MOLDED POLYURETHANE

SCHIOPPA



R 82 PE

Cast iron wheel, coated with high quality molded polyurethane. It has excellent abrasion and optimum resistance against shocks. It is widely used in floors slightly polluted by greases, salts, oils, solvents and paints, and as a main reference point it has the same high load capacity as cast iron wheels. This wheel is widely used by chemical, automobile, and autopart industries, among others. .

Hardness: 90 (± 5) Shore A.

Color: Yellow.

Temperature range: from -40° up to 80° C.

						Ref. Wheel				
3"	1.¼"	5/16"	37		125	R 312 PN				
4"	1.½"	7/16"	47		200	R 414 PN				
5"					250	R 514 PN				
6"					300	R 614 PN				
4"					200	R 414 PR				
5"	2"	5/8"	62			250	R 514 PR			
6"						300	R 614 PR			
4"						250	R 42 PR			
5"						325	R 52 PR			
6"						400	R 62 PR			
7"				500		R 72 PR				
8"	70	1"	78		550	R 82 PR				
9"					550	R 92 PR				
10"					700	R 102 PR				
6"					600	R 63 PR				
8"	100	17	62		800	R 83 PR				
10"					1000	R 103 PR				
12"					1200	R 123 PR				
6"					800	R 64 PR				
8"					1000	R 84 PR				
4"					2"	20	62		250	R 42 PE
5"									325	R 52 PE
6"									400	R 62 PE
7"									500	R 72 PE
8"									550	R 82 PE
9"	550	R 92 PE								
10"	70	25	78		700	R 102 PE				
6"					600	R 63 PE				
8"					800	R 83 PE				
10"					1000	R 103 PE				
12"	100	30	110		1200	R 123 PE				
6"					800	R 64 PE				
8"					1000	R 84 PE				
10"					1400	R 104 PE				
12"	125	35	134		1700	R 124 PE				
16"		2800			R 165 PE					
20"		3000			R 205 PE					